GK BLACKSPOT REMOVER & CLEANER

OVERVIEW

GK Black Spot Remover Is a high performance cleaner designed to remove black spots as well as organic and microbiological contaminants from porous surfaces such as stone, block paving and concrete.

BENEFITS

- Powerful and effective cleaner for stubborn areas of lichen and algae
- Does not alter the appearance of the surface
- Fast acting
- Low odour
- Solvent and acid free
- Biodegradable
- Professional strength

IMPORTANT INFORMATION

Do not use in wet weather, frost or if rain is forecast within the application period. If used when surface and air temperature is below 5ºC the effectiveness may be reduced and longer cleaning time may be required.

Keep pets away until the surface is fully washed and dry.

Ideal application temperature between 10ºC and 30ºC.

The longer the product is left to work (up to 24 hours) the brighter the surface will appear.

CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

PRODUCT CHARACTERISTICS

Colour	Clear
Odour	Pleasant Fragrance
Form	Liquid
PH	≈7
Solubility in Water	100% Soluble
Shelf Life	24 months from the date of manufacture in the original unopened container

APPLICATION

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory before commencing with the whole area.

Remove loose dirt, moss and other debris from the surface to be cleaned. A yard broom or firm bristle brush is ideal.

1. Apply product to a damp (not wet) surface with a low pressure garden sprayer, roller, brush, watering can or even a soft broom

2. Saturate the surface with a generous even coat at the following rates:
   Heavy soiling & Contamination: 3 - 4m² per litre
   Light soiling & Contamination: 5 - 6m² per litre

3. Depending on level of contamination leave Black Spot Remover & Cleaner to work for a minimum of 4 - 8 hours. For heavier contamination longer may be required, up to 24 hours. To determine the time required try a few spots before completing the project.

4. Rinse with high pressure washer or running water and a stiff deck brush.

GK Products UK, Rabart House, Pontsarn Road, Pant Industrial Estate, Merthyl Tydfil CF48 2TN
Tel: (+44) 3330 1245 7027
EMail: info@gkproductsuk.com