

INVISIBLE WOOD SEALER

**OVERVIEW**

Invisible Wood Sealer is a high performance, penetrating, repellent sealer. The specially designed formula penetrates porous wood surfaces such as; decking, fencing and timber surfaces.

Invisible Wood Sealer uses the latest technology to provide invisible protection with outstanding performance and durability.

BENEFITS

- Easy to use
- Provides hard wearing, invisible, protective against water penetration
- Allows the surface to breathe so moisture can escape
- Suitable for most timber surfaces
- No change to the texture or colour of the surface
- Resists the growth of mould and algae
- For use on horizontal and vertical surfaces
- Resists the growth of mould and algae
- Water based and alkaline resistant

IMPORTANT / LIMITATIONS

Keep children and pets away until the treatment is complete and the surface is completely dry.

Do not apply if rain is expected within 4 hours or before the surface is completely dry.

Do not apply to hot surfaces or in direct sunlight.

SURFACE PREPARATION

Surface should be clean and free from dirt, soiling mould and algae before applying. Treat any algae/mould and lichen using GK Pro, GK Fungicidal Solution or GK Greener Kleener.

Ideal application temperature should be between 10°C and 30°C.

Surface **MUST** be completely dry before application.

PRODUCT CHARACTERISTICS

Colour	White/Clear
Odour	Barely Perceptible
Form	Liquid
PH	6 - 8
Specific Gravity @ 25°C	1.01
Shelf Life	24 months from the date of manufacture in the original unopened container
Application Temperature	Min 5°C : Max 30°C
Coverage	Approx. 4 - 6 m ² per litre depending on the porosity of the surface

APPLICATION

This product is ready to use - do not dilute.

Shake container before use.

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption.

Ensure surface is thoroughly dry and dust free before application.

Apply a generous even coat with a brush, long pile roller or low pressure spray to saturation point.

Once the first coat starts to soak in, apply a further wet on wet coat. This method gives deeper penetration into the surface. Do not allow the product to dry in-between applications.

Avoid runs, drips or puddling by removing excess product from the surface using a clean lint free cloth

Leave to dry. Surface should be touch dry within 2 hours and fully dry after 24 hours.

For decking and flooring please allow 24 hours before subjecting to heavy traffic.

CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

STORAGE

KEEP OUT OF REACH OF CHILDREN.

24 months from the date of manufacture in original unopened container.

Keep in a dry place.

Do not store below 5°C. Keep out of direct sunlight and protect from frost.

PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)